



16Amp 230V

Model Name
**Automatic Transfer Switch
(ATS)**

Model Number
ATS-1623F-10N1



Meter True RMS Current Meter.

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Installed in Rack Horizontal

Power Action Automatic Transfer Switch

Event Alert Email, Trap

Option Device Temp./Humidity Probe

General

Output (10) IEC320 C13
Input (2) DIN49441 (Schuko) Inlet; Enclosed IEC320 C19 to Schuko plugs, 3 Meters power cord

Communication

DHCP Indication (1) Green LED
Output Status (2) Green LED
Input Status (2) Green LED
Network (1) RJ45 for Ethernet
Temp./Humidity (1) RJ11 for ENV probe connection
Identification 1 Digits Seven Segments for Identification
Meter 3 Digits Seven Segments

Power Information

Voltage +/- 2% @ 90V~260V
Active Power +/- 2% @ 50W~5000W
Apparent Power +/- 2% @ 50VA~5000VA
Frequency +/- 2% @ 45~65Hz
Power Factor +/- 0.02 @ 0.5~1.0
kWh Range: 0.001kWh ~ 99999.999kWh
Precision: +/-2% @ 50W~5000W, kh=1.0
Current Range: 0A ~ 20 A
Resolution: 0.1A
Precision: +/-2%+/-0.1AMP

Operation

Nominal Voltage 200V ~240V
On-Line Voltage 180V~ 262V
Frequency 50/60Hz
Max. Output Current 16 Amp
Transfer Time 8~16ms
Operation Temp. 0 ~ 40 Celsius degree
Humidity 0% ~ 90%
Size 260 x 432 x 44.45 mm
Net Weight 5 kg

