



19" RACKMOUNTED PDU

MTH - 1623K-08N1



IEC320 C20



IEC 320 C13



Description	
230V, 16A, 8 Outlets, Remote Current Monitoring	
Features	
Current Meter	Digital True RMS Current Meter
Power Monitor	Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm
Specification	
General	
Output	(8) IEC 320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker
Communication	
SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP
Operation	
Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 432 x 44 mm
Weight	2.5 kg
Regulatory Approvals	
CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, ICES-003	