

MTV-3223C-16N2



PDU Technology Specification

Description	
230V, 32A, 16 Outlets, Remote Current Monitoring	
Features	
Current Meter	Digital True RMS Current Meter
Power Monitor	Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm
Temp./Humidity	Option Accessory
Specification	
General	
Output	(14) IEC 320 C13 (2) IEC 320 C19
Input	(1) IEC 320 309 attached power cord, 3 meters long
Protection	(2) 16 AMP Circuit Breaker
Communication	
SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP
Operation	
Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	32 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	4 kg
Regulatory Approvals	CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, ICES-003



IE C60309
(32A 2P+E)



IEC 320 C13



IEC 320 C19

