



# 19" RACKMOUNTED PDU

**SWH-1623K-08N1**



## PDU Technology Specification

Description	
230V, 16A, 8 Outlets, Remote Current Monitoring, Remote Power Switch	
Features	
<b>Current Meter</b>	Digital True RMS Current Meter
<b>Power Monitor</b>	Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
<b>Protocols</b>	Http, Https, SNMP, DHCP, UDP
<b>Outlet Control</b>	Individual Outlet Control
<b>Power Delay</b>	Power On/Off Sequence can be Defined
<b>Alarm Thresholds</b>	User-Defined Alarm Thresholds for Warning and Overload
<b>Event Alert</b>	Email, Trap, Audible Alarm
Specification	
General	
Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker
Communication	
SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP
Operation	
Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 432 x 44 mm
Weight	3 kg
Regulatory Approvals	
UL 60950-1, UL Listed, CSA, cUL Listed, CB by UL CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006	



IEC320 C19



IEC 320 C13

