



Model Name
**Automatic
Transfer Switch
(ATS)**

Model Number
ATS-3223C-10N2



32Amp 230V

Meter True RMS Current Meter.

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Installed in Rack Horizontal

Power Action Automatic Transfer Switch

Event Alert Email, Trap

Option Device Temp./Humidity Probe

Protection Circuit Breaker

General

Output	(10) IEC320 C13
Input	(2) attached IEC309 32A 2P+E plugs,3 meters
Output Protection	(2) 16 AMP Circuit Breaker

Communication

DHCP Indication	(1) Green LED
Output Status	(2) Green LED
Input Status	(2) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
Identification	1 Digits Seven Segments for Identification
Meter	3 Digits Seven Segments

Power Information

Voltage	+/- 1% @ 80V~260V
Active Power	+/- 1% @ 50W~8000W
Apparent Power	+/- 1% @ 50VA~8000VA
Frequency	+/- 1% @ 50~65Hz
Power Factor	+/- 1% @ 0.1~1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/-1% @ 50W~8000W, kh=1.0
Current	Range: 0A ~ 32 A Resolution: 0.1A Precision: +/-1%

Operation

Nominal Voltage	200V ~240V
On-Line Voltage	180V~ 262V
Frequency	50/60Hz
Max. Output Current	32 Amp
Transfer Time	8~16ms
Operation Temp.	0 ~ 45 Celsius degree
Humidity	0% ~ 90%
Size	260 x 432 x 44.45 mm
Net Weight	6.1 kg

Regulatory Approvals

