

SWV-3223C-16N2



PDU Technology Specification



IE C60309
(32A 2P+E)



IEC 320 C13



IEC 320 C19



Description	
230V, 32A, 16 Outlets, Remote Current Monitoring, Remote Power Switch	
Features	
Current Meter	Digital True RMS Current Meter
Power Monitor	Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Outlet Control	Individual Outlet Control
Power Delay	Power On/Off Sequence can be Defined
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Temp./Humidity	Option Accessory
Event Alert	Email, Trap, Audible Alarm
Specification	
General	
Output	(14) IEC320 C13 (2) IEC320 C19
Input	(1) IEC320 309 attached power cord, 3 meters long
Protection	(2) 16 AMP Circuit Breaker
Communication	
SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP
Operation	
Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	32 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm